

PERFORMANCE CHART

SUBMERSIBLE CUTTER SEWAGE PUMPS JSDK Series

Three Phase 380 Volts, 50 Hz, A.C. Supply



Construction		No.	PART	MATERIAL
		1	Cable	VCT
		2	Cable Hood	PVC
		3	Handle	SS 304
		4	Motor Cover	FG 200
		5	Elec. Stamping	CRNO
		6	Bracket	FG 200
		7	Oil Chamber	FG 200
		8	Pump Casing	FG 200
		9	Impeller FG 200	
		10	Mech. Seal	CC/SC
		11	Oil Seal	NBR
		12	Cutter edge	Tungsten
		13	Bearing	NTN
		14	Protector	(T.I./YAMADA)
		15	Shaft	SS 410
		16	Motor Housing	SS 304

2-Pole, 2900rpm

MODEL	HP / K.W.	PHASE	DEL. SIZE	DISCHARGE IN lpm					
				lpm	200	400	600	800	1000
JDSK - 20	2.0 / 1.5	3	2"	TOTAL	13	9	4	-	-
JDSK - 30	3.0 / 2.2	3	3"	HEAD	16	13	8	2	-
JDSK - 50	5.0 / 3.7	3	3"	IN	19	15.5	11.5	6	-
JDSK - 75	7.5 / 5.5	3	4"	MTRS	24	20	15	12	4